SERVO ® PRODUCT DATA SHEET SERVO BRAKE FLUID SUPER HD



GRADES AVAILABLE - SERVO BRAKE FLUID SUPER HD

DESCRIPTION

Servo Brake Fluid Super HD is heavy duty hydraulic brake fluid which ensures long service life of the brake fluid and components of brake mechanism. It remains clear and uniform fluid under extreme cold climatic conditions, enabling satisfactory operation of brake systems.

It is fully compatible with rubber seals used in Hydraulic Brake Systems. It also lubricates the moving parts of the brake system very effectively.

APPLICATION

Servo Brake Fluid Super HD is designed for use in modem brake system of automotive vehicles operating in heavy duty conditions The higher boiling point of this product provided greater safety factor while driving at high speed with heavy load or in hilly areas where frequent braking generates higher temperatures in the brake system.

Servo Brake Fluid Super HD is recommended for various hydraulic brake systems including disc type.

PERFORMANCE BENEFITS

Servo Brake Fluid Super HD

- Provides very high safety factor during driving at high speed in city and under heavy load in hilly regions
- Provides excellent protection against corrosion to iron, non-ferrous metals and zinc alloys
- Has longer service life, due to excellent oxidation stability

PERFORMANCE STANDARDS

Servo Brake Fluid Super HD meets the following specification:

- SAE J 1703
- FMVSS 116.3 DOT 3
- IS:8654-1986
- •

MANUFACTURERS APPROVAL

Servo Brake Fluid Super HD is approved by TELCO, Maruti, Daewoo Motors, etc.

CHARACTERISTICS

Appearance	Clear Homogeneous red liquid		
Equilibrium Reflex Boiling Point, °C Min.	205		
Kinematic Viscosity, cSt			
@ (-) 40°C, Max.	1500		
@ 100 ° C, Min.	1.5		
pH Value	7.0-11.5		

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.