SERVO ® PRODUCT DATA SHEET SERVO PRIDE ALT 15W-40



GRADES AVAILABLE - SERVO PRIDE ALT 15W-40

DESCRIPTION

Servo Pride ALT 15W-40 is premium commercial diesel engine oil. The oil is designed for the most severe performance requirements of new generation diesel engines for on and off highway operations. It assures outstanding protection against high temperature engine deposits, oil degradation, oil thickening and corrosion resistance. The oil is having excellent shear stability to maintain viscosity under severe, high temperature operations. It exhibits outstanding control on soot induced thickening and soot induced wear.

APPLICATION

Servo Pride ALT 15W-40 is recommended for new generation commercial diesel vehicles of Ashok Leyland complying to Bharat Stage II & III Emission Norms. It is especially compounded for use with diesel fuel ranging in sulphur content upto 0.5% by wt.

PERFORMANCE BENEFITS

- # Reduced engine scuffing and bore polishing.
- # High engine cleanliness.
- # Maximum protection from wear and deposits.
- # Suitable for mixed fleet operation.
- # Improved control of oil consumption.
- # Easier cold starting.
- # Excellent all weather performance due to improved cold weather properties.
- # Has the potential to doubled the oil drain intervals compared to current diesel engine oils.

PERFORMANCE STANDARDS

- * API CH-4
- * MB 228.5

APPROVAL

Ashok Leyland Ltd, Chennai.

CHARACTERISTICS

SAE GRADE	ALT 15W-40		
Kinematic Viscosity, cSt @ 100°C	13.5 – 15.5		
Viscosity Index, Min.	135		
TBN, mg KOH/g	10.0 – 11.5		
Flash Point, (COC)°C, Min.	200		
Pour Point °C, Max.	(-) 24		

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR: