

SERVO[®] PRODUCT DATA SHEET

SERVO PRIDE TC 15W-40



GRADES AVAILABLE - SERVO PRIDE TC 15W-40

DESCRIPTION

Servo Pride TC 15W-40 is a premium quality, commercial multipurpose diesel engine oil. The oil is designed for the most severe performance requirements of modern, highly rated turbo charged diesel engines for the road transport fleet applications. It assures outstanding protection against high temperature engine deposits, oil degradation, oil thickening and corrosion resistance. The oil is having excellent shear stability to maintain viscosity under severe, high temperature operations.

APPLICATION

Servo Pride TC 15W-40 is recommended for commercial diesel vehicles for both National and International Heavy duty highway equipments. This oil meets API CG-4 / SG service classification for modern and low emission diesel engines. This oil is also recommended for Gasolene Engines allowing to be used in mixed fleet operations.

PERFORMANCE BENEFITS

- Reduced engine scuffing & bore polishing.
- High engine cleanliness.
- Maximum protections from wear and deposits.
- Suitable for mixed fleet operation.
- Improved control of oil consumption.
- Easier cold starting.
- Excellent all weather performance due to improved cold weather properties.
- Catalytic Converter compatible.

PERFORMANCE STANDARDS

- * API CF-4 / SG
- * MB 228.1

CHARACTERISTICS

SAE GRADE	15W-40
Kinematic Viscosity, cSt @ 100°C	14.0 – 15.0
Viscosity Index, Min.	135
TBN, mg KOH/g	8.5 – 11.5
Flash Point, (COC)°C, Min.	200
Pour Point °C, Max.	(-) 24

HEALTH & SAFETY

These oils are unlikely to present any significant health or safety hazard when properly used in the recommended application and good standards of industrial and personal hygiene are maintained.

For further information please contact our nearest office OR:

Technical Services Dept., Indian Oil Corporation Ltd., G-9, Ali Yavar Jung Marg, Bandra (East), Mumbai – 400 051

E-Mail: tservices@indianoil.co.in OR tech_services@indianoil.co.in

